



Instructions for Bar SAC™

- I. Pull strap with adjustable male end through guides.
- 2. Set The Bar SAC[™] on headlight and wrap the straps around the handle bars.
- Clip the male end into the female end and pull tight.
- 4. You can cut and melt the excess strap, but be sure to leave enough for any other applications you may have.
- If you would like the Bar SAC[™] at a different angle, don't run the strap through the guides.
- 6. You can easily clip the Bar SAC[™] to other SAC[™] products.





Instructions for Jam SAC™



I. Pack the waterproof bag and pull drawstring tightly.



2. Place the free end of the compression system over the drawstring opening so all four compression straps are in line. Compress the bag as far as desired to make a firm pack.



3. Place the sissy bar cover over your sissy bar and pull strap tight. Use the long straps to secure Jam SAC™ to turn signal struts or other secure location. OR: Pull male ends of the two long straps tight and attach Jam SAC™ to other SAC™ products and use SAC Net™ to further secure load and other belongings.

Instructions for Camp SAC™

- I. Remove tent and sleeping bag cover bags. (Don't throw cover bags away).
- 2. Stuff your tent and tent fly into the bottom of the bag.
- 3. Place the two air mattresses side by side on top of the tent.
- 4. Stuff the two sleeping bags around the air mattresses and place the two pillows on top.
- 5. Follow steps 1-3 from the Jam SAC™ instructions above.
- 6. Attach the SAC Net[™] to the D-rings on the Camp SAC.[™] Put the tent poles and stakes into the tent bag and thread the bag through the spaces in the SAC Net.[™] Tie the bag to the SAC Net.[™]

Please Note

Your Camp SAC $^{\text{TM}}$ weighs 24 lbs. full, so be sure to load your motorcycle according to the manufacturer's manual. Make sure your tire pressure is correct for your load and your motorcycle is balanced. If you are uncertain of how to properly load your motorcycle please see your dealer for help.

